

Gvision LCD Monitor Spring Ice Series

- Product Specification -

Configuration		S2FS & S2HS
LCD Display		12.1" DSTN / TFT LCD panel
Display Size (HxV mm)		246(H) x 184.5(v)mm
Max. Resolution		SVGA 800x600
Contrast Ratio		TFT - 250 : 1 (typical)
		DSTN - 40 :1 (typical)
Brightness		TFT - 120cd/m2 (typical)
		DSTN - 90cd/m2 (typical)
Response Time		TFT - 50 ms (typical)
		DSTN - 150 ms (typical)
Display Color		TFT - 16M
		DSTN - 64K
Viewing Angle	L/R	TFT +50°~-50° (typical)
		DSTN +35°~-35° (typical)
	U/D	TFT +40°~-25° (typical)
		DSTN +35°~-20° (typical)
PC Interface	Video	RGB analog 0.7Vpeak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 640X350 (70/85 Hz)
		VGA 720X400 (70/85Hz)
		VGA 640X480 (60/72/75/85 Hz)
		SVGA 800x600 (56/60/72/75/85 Hz)
		Mac. 832 x 624 (75Hz)
Video-In (optional)		S & RCA Connecor (NTSC/PAL Auto-detect)
Touch Panel (optional)		Capacitive / Resistive / Touch Pen type with RS232 connector
Signal Connector		D-sub 15 pin
Front Control		Power on/off with LED, Menu, Select (Up, Down), Adjustment (+,-)
OSD		Contrast, Brightness, Phase, Clock, Track, R.G.B.
		contrast, H-position, V-Position, Recall, Auto-tune
Plug & Play		DDC1/2B
Power Adapter		Input AC 100-240V, 50-60Hz;Output DC 12V / 3A
Operating Conditions	Temperature	5°C~35°C (41°F~95°F)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~60°C (-4°F~140°F)
	Humidity	10%-90% (no condensation)
Dimensions	Open Frame	302(H) x 236.5(W) x 39.7(D)mm
	Panel Mount	328.9(H) x 248.5(W) x 43.4(D)mm
Weight (lbs)	Open Frame	4.4 (net)
	Panel Mount	5.06 (net)

* Specifications are subject to change without notice.

Catch the wave of the future - Now!

Gvision USA Inc.

1582 Parkway Loop, Suite C, Tustin, CA 92780

