

L7PH 17" LCD Monitor

Product Specifications

SPECIFICATIONS

L7PH

LCD Display Area		17.0" TFT Active Matrix Panel
Display Size (HxV)		13.3"x10.6" (337.9x270.3 mm)
Pixel Pitch (HxV)		0.264x0.264 mm
Max. Resolution		SXGA 1280x1024
Contrast Ratio		350:1 (typical)
Brightness		250 cd/m ²
Response Time		40 ms
Display Color		16M
Viewing Angle	L/R	160°
	U/D	+65°~-80°
Input Signal	Video	RGB analog 0.7V peak to peak
	Sync	TTL Positive or Negative
Display Mode		VGA 720x400 (70 Hz) VGA 640x480 (60/70/72/75 Hz) SVGA 800x600 (56/60/72/75 Hz) XGA 1024x768 (60/70/75 Hz) SXGA 1280x1024 (60/75 Hz)
Signal Connector	Analog	D-sub 15 pin
	Digital	24 -pin DVI (optional)
Front Control		Power on/off with LED, Menu, Select, Adjustment (+,-)
Plug and Play		DDC 1/2B
Power Adapter		Input AC 100~240V, 50~60Hz; output DC 12V / 4A
Operating Conditions	Temperature	41°F ~ 95°F (5°C ~ 35°C)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-4°F ~ 140°F (20°C ~ 60°C)
	Humidity	10%-90% (no condensation)
AudioSystem	Speakers	2W / Per Channel Driver
Dimensions (HxWxD)		21.08"x20.8"x9.9" (535x528x252mm)
Weight (Net)		15.2lb (6.88kg)
Optional Module		Analog, Dual inputs, Adjustable arm, Photo Stand, Black bezel
Certifications		C-UL, FCC, CE, TUV/GS, BSMI, EPA, NUTEK, TCO

Specifications are subject to change without notice.



Catch the wave of the future!

20532 Crescent Bay Dr. Suite 104
Lake Forest, CA 92630
Ph: 949-586-3338 Fax: 949-586-3398
www.gvision-usa.com

