

PST-7000 SERIES



Overview

The powerful PST7000 carries the Intel® 1.2G Celeron™ CPU and an abundance of unique features for which POSIFLEX is renowned. Covered service openings provide easy access to jumpers, RTC Battery, HDD and memory. These openings also allow access to an internal IDE connector, minimizing the labor needed for software serviceability.

Modular double and quad key design allows positioning anywhere on the keyboard. The PST-7000 supports dual independent video output, and it's built in UPS helps to prevent problems caused by unexpected power loss.

Specifications:

PST 7000 Specifications	
CPU	Intel® Celeron™ 1.2 GHz
Memory	64MB, expandable to 512MB via 2 DIMM Sockets
NVRAM	32KB Non-Volatile
Cache Memory	2nd Level Cache in CPU
FDD	1.44MB
Display	12" TFT Color LCD
HDD	20GB up
OS	Option for Window 9x/2000/ XP Professional / NT preloaded
Magnetic Stripe Reader (Optional)	2 Tracks / 3 Tracks / JIS II option
Keyboard	112 Key, fully programmable with daisy chain architecture or QWERTY keyboard w/ 53 programmable keys (Optional)
Key Switch Control	6 position key control for 5 pages, key lock and answer back code control
Interfaces – Parallel	1 port, bi-directional, supports ECP/EPP
Interfaces – Serial	4 Serial with +5V/+12V power on COM2, COM3 and COM4 can be enable / disable
Keyboard Port	6 pin mini DIN PS/2 KB connector
Cash Drawer Port	1 port controls 2 devices (shared with COM1)
Network	1 UTP 10/100 BASE-T Ethernet LAN
Printer Power Port	24 VDC / 2A
Customer Display	RJ45(10 pin) connector, controlled through COM1
USB	2 x USB ports
Built-In IDE	Supports up to Ultra DMA/66
Expansion IDE Port	Option slim CD ROM
Expansion Slot	1 x ½ length PCI Bus and 1 x ISA Bus slot
Power Off Function	Controllable by power switch or software through remote LAN or Modem
Model Types	PST-7150 : With QWERTY (All systems have UPS functionality and Y2K compliance)
Dimensions	LCD : 408mm(W) x 465mm(D) x 355mm(H) 16.1" x 18.0" x 14.0"
Weight	PST with LCD : 10.0kg (22.03 lbs)

POSIFLEX™

1280 San Luis Obispo Avenue
Hayward, California 94544 USA
tel : 510-429-7097
fax : 510-475-0982
e-mail : sales@posiflexusa.com
www.posiflexusa.com